




Product Service

CERTIFICATE

No. Z2 099333 0043 Rev. 29

Holder of Certificate: LONGi Green Energy Technology Co., Ltd.
No. 388, Middle Hangtian Road
Chang'an District
710100 Xi'an City, Shaanxi
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product: Crystalline Silicon Terrestrial Photovoltaic (PV) Modules
Mono-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 704061802007-30

Valid until: 2029-07-10

Date, 2025-10-31

(Zhulin Zhang)

CERTIFICATE

No. Z2 099333 0043 Rev. 29

Model(s):

LR5-72HBD-xxxM (xxx=500-565, in step of 5)
 LR5-72HBD-xxxMa (xxx=500-565, in step of 5)
 LR5-72HBD-xxxMc (xxx=500-565, in step of 5)
 LR5-72HBD-xxxMc1 (xxx=530-565, in step of 5)
 LR5-72HBD-xxxMc2 (xxx=530-565, in step of 5)
 LR5-72HBD-HD-xxxM (xxx=500-565, in step of 5)
 LR5-72HIBD-xxxM (xxx=500-565, in step of 5)
 LR5-66HBD-xxxM (xxx=475-515, in step of 5)
 LR5-66HIBD-xxxM (xxx=475-515, in step of 5)
 LR5-60HBD-xxxM (xxx=435-470, in step of 5)
 LR5-60HIBD-xxxM (xxx=435-470, in step of 5)
 LR5-54HBD-xxxM (xxx=390-425, in step of 5)
 LR5-54HIBD-xxxM (xxx=390-425, in step of 5)
 LR5-54HABD-xxxM (xxx=395-420, in step of 5)
 LR5-78HBD-xxxM (xxx=570-605, in step of 5)
 LR5-54HABB-xxxM (xxx=395-415, in step of 5)
 LR5-54HIBB-xxxM (xxx=395-415, in step of 5)
 LR5-72HGD-xxxM (xxx=540-595, in step of 5)
 LR5-72HGD-xxxMc (xxx=560-595, in step of 5)
 LR7-72HGD-xxxM (xxx=565-635, in step of 5)
 LR5-72HJD-xxxM (xxx=575-595, in step of 5)
 LR5-72HTDR-xxxM (xxx=550-600, in step of 5)
 LR5-72HTD-xxxM (xxx=550-600, in step of 5)
 LR5-54HTD-xxxM (xxx=415-450, in step of 5)
 LR8-66HGD-xxxM (xxx=595-645, in step of 5)
 LR8-48HGD-xxxM (xxx=430-465, in step of 5)
 LR7-72HTDR-xxxM (xxx=585-655, in step of 5)
 LR7-66HTDR-xxxM (xxx=535-575, in step of 5)
 LR7-60HTDR-xxxM (xxx=485-525, in step of 5)
 LR7-54HTDR-xxxM (xxx=435-475, in step of 5)
 LR7-72HYD-xxxM (xxx=625-660, in step of 5)
 LR7-72HVD-xxxM (xxx=610-670, in step of 5)
 LR7-48HGD-xxxM (xxx=385-415, in step of 5)
 LR7-54HGBB-xxxM (xxx=440-460, in step of 5)
 LR8-66HYD-xxxM (xxx=625-670, in step of 5)
 LR7-54HVD-xxxM (xxx=455-500, in step of 5)
 LR5-78HGD-xxxM (xxx=610-645, in step of 5)
 LR7-72HJD-xxxM (xxx=650-680, in step of 5)
 LR7-66HJD-xxxM (xxx=595-625, in step of 5)
 LR7-60HJD-xxxM (xxx=540-570, in step of 5)
 LR7-54HJD-xxxM (xxx=485-515, in step of 5)
 LR7-48HJD-xxxM (xxx=430-460, in step of 5)
 LR7-36HJD-xxxM (xxx=320-350, in step of 5)
 LR7-32HJD-xxxM (xxx=280-310, in step of 5)
 LR8-66HVD-xxxM (xxx=625-670, in step of 5)
 LR7-60HVD-xxxM (xxx=520-550, in step of 5)
 LR8-54HGBB-xxxM (xxx=490-510, in step of 5)
 LR7-72HVBB-xxxM (xxx=625-655, in step of 5)
 LR7-54HVBB-xxxM (xxx=460-495, in step of 5)
 LR7-72HVDF-xxxM (xxx=610-670, in step of 5)
 LR7-72HJBB-xxxM (xxx=650-680, in step of 5)
 LR7-66HJBB-xxxM (xxx=590-620, in step of 5)
 LR7-60HJBB-xxxM (xxx=535-565, in step of 5)
 LR7-54HJBB-xxxM (xxx=480-510, in step of 5)
 LR7-48HJBB-xxxM (xxx=425-455, in step of 5)
 LR7-36HJBB-xxxM (xxx=315-345, in step of 5)
 LR7-32HJBB-xxxM (xxx=280-310, in step of 5)
 LR8-66HVDF-xxxM (xxx=625-670, in step of 5)
 LR8-66HTD-xxxM (xxx=600-655, in step of 5)
 xxx is standing for rated output power at STC.

CERTIFICATE

No. Z2 099333 0043 Rev. 29

Parameters:

Safety Class:	Class II
Maximum System Voltage:	1500 V DC
Fire safety Class:	Class C according to UL790
Construction:	Framed or frameless, with Junction box, Cable and Connectors.

Tested according to:

IEC 61215-1:2021
IEC 61215-1-1:2021
IEC 61215-2:2021
IEC 61730-1:2023
IEC 61730-2:2023
IEC 62716:2013